

PCC+ Print Servers Procurement Information

ITSC is advising sites to use Informatix (ILC) in Salt Lake City for the purchase, configuration, and technical assistance with their Print Servers. Two print servers are strongly recommended to provide system redundancy.

Cost

ILC sells systems in pairs. As of 7/1/05, a complete PAIR of print servers (baseline system) with Office 2003, WIN XP Pro, and the PCC+ software installed and tested is priced at **\$2,997.00**. Prices are subject to change based on fluctuations in component prices from ILC suppliers. Prices also may vary depending on the configuration desired by the site.

ILC print server configuration

- Base systems arrive in a tower configuration with a Pentium IV 3.X GHz CPU, 512MB RAM, 80 GB Hard Drive, one each 17" Monitor, PS2 Mouse and Keyboard, KVM switch and cables in lieu of a second monitor, mouse/keyboard.
- Optional 1GB RAM available at \$50 per Print Server, \$100 for both
- Rack mounts are available in 3 models for "shelf" mounting in a rack
- Full Rack mount chassis with slide-out rails are also available in 2U, 3U and 4U configurations

Vendor Data

VENDOR:	INFORMATIX LABORATORIES CORP	EIN NO:	1841409845
		DUNS...:	
ACCT...:	CHECKING	BANK #:	124000737
		DEPOSITOR:	445010003272
PARENT:		C-DIST:	
CITY #:	TELECOM #:	TYPE...:	(A3) OTHER SMALL BUSINESS
W-OWND:	NO	LSA...:	
SBS...:	YES	SIZE...:	251-500
V-CODE:	ORGANIZATION	PROFIT:	
N-PROF:	NO	GEOLOC:	
SMALL BUS:	SMALL BUSINESS CONCE	OTHER	
MAILING ADDRESS	BILLING ADDRESS	REMIT TO ADDRSS	
-----	-----	-----	
774 EAST 3300 SOUTH STE 200	SAME AS ABOVE	774 EAST 3300 SOUTH SUITE 200	
SALT LAKE CITY		SALT LAKE CITY	
UTAH 84106		UTAH 84106	
801-474-1600		801-474-1600	
FAX:		801-485-9600	

Credit cards are now accepted for payment.

For further information, contact:

Gordon Moreshead
ILC
774 E, 3300 S, Ste 200
Salt Lake City, UT 84106
801-474-1600 x227
gmoreshead@informatixcorp.com



Go to <http://www.ihs.gov/CIO/pccplus/> for
PCC+ implementation information, or contact Clarence Smiley MPH, MT (ASCP)
Clarence.Smiley@ihs.gov; (800)-545-1880 x6245



Technical Specifications for Print Servers

If the site chooses to purchase its own print servers:

- Print Server(s): A 1.0+ GHz PC with at least 512MB RAM, 30 GB hard drive, 10/100 Ethernet card. The print server must be able to run “off the shelf” copies of Microsoft Windows 2000 and Microsoft Office 2000. **Note:** Installing a second (backup) print server with identical configuration is strongly recommended.

Minimum requirements.

- Intel PIII 733 MHz Processor
 - 56K V.90 Fax/Modem
 - AGP VGA 8m Video Adapter
 - 10/100 Smart NIC (Intel Or 3 Com)
 - Intel Mother Board
 - Micron Memory (Or Equal Quality)
 - ECP/EPP Printer Port
 - 128Mb -100MHz SDRAM
 - 10 Or More GB Hard Drive
 - 15” VGA Monitor, .28 Digital Display
 - 45x CDROM
 - 1.44 Floppy Disc Drive
 - 104 PS/2 Keyboard
 - Logitech PS/2 Internet Mouse
 - 2 Year Hardware Warranty
 - Ms Windows 2000 Pro
 - Ms Office 2000 SBE
 - Port Switch And Cables For Ps/2 Keyboard, Mouse & VGA Monitor
- Print Server software: A licensed, “off the shelf” copy of the Microsoft Windows XP Pro and Microsoft Office 2003 for each print server. Includes one set of official MS CD-ROM media and one set of licenses without media per pair of print servers. (Even though PCC+ has been successfully tested on Windows NT 4.0 and Office 97, we do not recommend these products and will not support them.). **Note:** some hardware vendors such as Compaq pre-load their own *proprietary* versions of the Windows operating system on their computers. Proprietary versions of Windows 2003 cannot be guaranteed as compatible with the PCC+ application. Therefore, they are not recommended and will not be supported by OIT. **Note:** PCC+ v2.5 will NOT operate properly with Office 98.
 - **Connectivity freeware for the Print Server:** VNC (remote control software) and WS-FTP (FTP service).



Go to <http://www.ihs.gov/CIO/pccplus/> for
PCC+ implementation information, or contact Clarence Smiley MPH, MT (ASCP)
Clarence.Smiley@ihs.gov; (800)-545-1880 x6245

